



OPRAWY WEWNĘTRZNE
INDOOR LUMINARIES / DECKENLEUCHTEN



OPRAWA DOWNLIGHT LED
LED DOWNLIGHT
LED ALLGEMEINBELEUCHTUNG

DME



DESCRIPTION / BESCHREIBUNG / DANE OPRAWY

W	Power / Leistung / Moc	35W / 45W
lm	Flux / Lichtstrom / Strumień	2700lm / 3800 lm
∠	Beam angle / Abstrahlwinkel / Kąt	45°
⚙	CRI	Ra > 80
V	AC	100-240V
⚙	Control / Steuerung / Sterowanie	ON/OFF
	Optional / Wahlweise / Opcjonalnie	DALI
IP	Protection / Schutzart / Szczelność	IP 65
🏠	Housing / Gehäuse / Obudowa	aluminium
🎨	Color / Farbe / Kolor	<input type="checkbox"/> white
🔧	Fixing / Montaż	Recessed / Podtynkow



CCT / FARBE / BARWA [K]

W	3000 K
D	4000 K
A	5000 K
B	5700 K



INDEX SYSTEM

	POWER	TEMP	CONTROL
DME	W	K	DALI
	35	W	OPTIONAL FEATURES WAHLWEISE / OPCJONALNIE
	45	D	
		A	
		B	

DALI DALI CONTROL
Standard: ON / OFF
Optional / Wahlweise: DALI

DME					
INDEX INDEKS	POWER LEISTUNG MOC	FLUX LICHTSTROM STRUMIEN	BEAM ANGLE ABSTRAHLWINKEL KĄT PADANIA	CRI EFFIZIENZ WYDAJNOŚĆ	CCT FARBE WYDAJNOŚĆ
DME 35 W	35 W	2500 lm	45°	Ra min. 80	3000 K
DME 35 D	35 W	2700 lm	45°	Ra min. 80	4000 K
DME 35 A	35 W	2970 lm	45°	Ra min. 80	5000 K
DME 35 B	35 W	2950 lm	45°	Ra min. 80	5700 K
DME 45 W	45 W	3480 lm	45°	Ra min. 80	3000 K
DME 45 D	45 W	3800 lm	45°	Ra min. 80	4000 K
DME 45 A	45 W	3900 lm	45°	Ra min. 80	5000 K
DME 45 B	45 W	3850 lm	45°	Ra min. 80	5700 K

